

TruTool:

TSC 100 Slat Cleaner



Simple, one-man operation

The TruTool TSC 100 Slat Cleaner uses a unique process to thoroughly clean the slag that accumulates on slats from normal day-to-day use. Using teeth to remove the slag instead of rollers, it cleans the sides of the slats as well as the hard-to-reach spaces in between. The slat cleaner design enables easy, one-man operation and automatically adjusts to accommodate different slag thicknesses. In addition, the operator can begin cleaning in any slat row and move the tool right up to the pallet frame. If the slat cleaner is being used on a flatbed laser machine with a pallet changer, cleaning can be done during production and without having to remove any slats.

Benefits at a glance

- Suitable for use with a variety of materials: stainless steel, mild steel and aluminum
- Best cleaning results due to the use of stainless steel teeth
- Can be used on laser machines with up to 8 kW laser power
- Can be operated by a single person
- Cleaning takes place while operation is running (on flatbed laser machines with a pallet changer)



Consistent performance to prolong the life of your slats

Even the most persistent stainless steel slag can be removed with the TruTool TSC 100 Slat Cleaner, as well as heavy slag from a variety of other materials. It also provides the flexibility to clean a specific area or the entire surface in a timely manner. For example, a 5'x10' area takes only 30 minutes to clean.

Consistent maintenance cleaning guarantees a long service life for your slats, and the TruTool TSC 100 Slat Cleaner can clean almost all conventional flatbed laser machines. By prolonging the life of your slats, the slat cleaner quickly pays for itself.

Technical data	
Support slat thickness	0.08 - 0.15 in.
Max. slag thickness	1 in.
Min. spacing between support slats	1.3 in.
Working speed	13 - 26 in/min
Rated input power	1200 W
Weight	45 lbs.

Accessories		
Included accessories		
Cleaning tool No. 3	0.12 - 0.15 in.	Included
Handle (complete)		Included
Transport wheels		Included
Seal (set of 2)		Included
External seal (set of 2)		Included
Available wear parts		
Cleaning tool No. 2 (set of 2)	0.08 - 0.11 in.	1644868
Cleaning tool No. 3 (set of 2)	0.12 - 0.15 in.	1644867
Carbon brush (set of 2)	110 - 120 V	1898534
Seal (set of 2)		1633583
External seal (set of 2)		2046587

