INTRODUCING
THE NEW RANDOM ORBITAL SANDER FROM SIOUX TOOLS.

HANDS DOWN, THE MOST COMFORTABLE SANDER MADE.

You've got limited resources and even less time to waste. We understand. If you're going to consider a new tool, it better have something going for it; something besides more horsepower.

SIOUX

Introducing the new random orbital sander from Sioux Tools. Hands down, it's the most comfortable pneumatic sander ever developed...no matter who is handling it.

DOBCO EQUIPMENT LTD. 905-672-5557 sales@dobcoeqp.com www.dobcoeqp.com
DOBCO EQUIPMENT LTD. 905-672-5557 sales@dobcoeqp.com www.dobcoeqp.com

A CONCEPT SO SIMPLE, ANYONE CAN GRASP IT.

UNIVERSAL GRIP – ONE GRIP FOR ALL USERS

- Asymmetrical and soft textured for a more natural feel.
- Rotates through 24-positions in 15 degree increments to accommodate various hand sizes and shapes and adapts for right- or left-handed users.



NATURALLY CONTOURED POWER LEVER

- Smoother S-shape fits more comfortably in the palm. And the natural hand position engages the power, helping to reduce fatigue.

USER FRIENDLY LOCK RINGS

- Color-coded and dual embossed allowing you to quickly and accurately identify orbit diameter at a glance.
- Lock rings are also externally mounted, making the sander easy to disassemble and service.

INTELLIGENTLY DESIGNED MOTOR

- Dual vibration dampers dramatically reduce vibration and fatigue.
- Patented dust shield prevents airborne particulates from entering the motor housing and bearings and improves overall life.
- Heavy duty motor generates 12,000 rpm (no-load) with pads up to 6" in diameter.



ADVANCED SPINDLE DESIGN

- The spindle is stepped to accommodate a larger bottom bearing. The larger bottom bearing results in longer life.
- By precision balancing the spindle crank, we were able to reduce motor vibration even further.

EASY TO SERVICE

- Molded orientation mark aligns the motor to the housing for easy assembly.
- A single center sealing o-ring replaces hard-to-handle inlet rings, making this one of the easiest motors to install and service.

SPECIFICATIONS

CE

Power	0.25 hp (0.19 kW)
Free Speed	12,000 RPM
Air Consumption, Free Speed	13 SCFM (6 l/s)
Sound Level	81 dBA
Spindle Thread	5/16"-24
Height	3.26" (83mm)
Weight	1.5 Lbs (0.7 kg)

GENERAL

Air Inlet Size: 1/4" NPT
Recommended Hose Size: 3/8" (10mm)
Performance rated @ 90 psig (6.2 bar) air pressure

Dobco Equipment Limited
1-2430 Lucknow Drive,
Mississauga, Ontario
L5S 1V3 Canada

905.672.5557

sales@dobcoeqp.com

DOBCO EQUIPMENT LTD. 905-672-5557 sales@dobcoeqp.com www.dobcoeqp.com

DOBCO EQUIPMENT LTD. 905-672-5557 sales@dobcoeqp.com www.dobcoeqp.com

SIOUX

Sioux Tools. Tools for the way you work.

FORM#ZML0098
PRINTED IN USA
7/05 250

ISO 9001 CERTIFIED