

RAPID REVERSE

DRILLS

SCREWDRIVERS

IMPACT DRIVER

Compact 0.4 hp
Full-Size 0.6 hp & 1.0 hp

**2 NEW
DRILLS!**

Push for Momentary Reverse
Push & Turn for Continuous Reverse



SDR4P20R2RR

SSD4P26SRR

**4 NEW
SCREW-
DRIVERS!**



Rapid Reverse Signature Series Drills



SDR4P20R2RR



SDR6P20R3RR



SDR10P20RK3R



SDR10P20R3RR

Features:

- Rapid Reverse
- Feathering Trigger
- Ergonomic Grip
- Light Weight Aluminum Housing
- Easy to Maintain 'Drop-in Motor'
- Low Noise
- 3 Planet Gear System
- Fast and Convenient Reversing with Top Button
- Momentary Reverse or Twist-Lock Constant Reverse



Model Number	Chuck Capacity		Free Speed rpm	Weight		Length		Side To Center		Max. Air Consumption		Spindle Thread
	in	mm		lb	kg	in	mm	in	mm	cfm	l/s	
0.4 hp (0.30 kW) – Keyed Chuck												
SDR4P20R2RR	1/4	6	2000	1.7	0.7	6.0	150	0.7	16.8	20	10	3/8"-24
SDR4P30R2RR	1/4	6	3000	1.7	0.7	6.0	150	0.7	16.8	20	10	3/8"-24
0.6 hp (0.45 kW) – Keyed Chuck												
SDR6P20R3RR	3/8	10	2000	2.3	1.00	6.3	160	0.8	20	25	12	3/8"-24
SDR6P25R3RR	3/8	10	2500	2.3	1.00	6.3	160	0.8	20	25	12	3/8"-24
0.6 hp (0.45 kW) – Keyless Chuck												
SDR6P7RK4RR	1/2	13	700	3.0	1.25	8.8	224	0.8	20	25	12	1/2"-20
SDR6P20RK3RR	3/8	10	2000	2.4	1.25	6.8	173	0.8	20	25	12	3/8"-24
SDR6P20RK4RR	1/2	13	2000	2.7	1.20	7.2	183	0.8	20	25	12	1/2"-20
SDR6P25RK3RR	3/8	10	2500	2.4	1.25	6.8	173	0.8	20	25	12	3/8"-24
SDR6P25RK4RR	1/2	13	2500	2.7	1.20	7.2	183	0.8	20	25	12	1/2"-20
1 hp (0.75 kW) – Keyed Chuck												
SDR10P5R4RR	1/2	13	500	3.6	1.63	8.8	224	0.8	20	30	14	1/2"-20
SDR10P20R3RR	3/8	10	2000	2.6	1.15	7.6	195	0.8	20	30	14	3/8"-24
SDR10P25R3RR	3/8	10	2500	2.6	1.15	7.6	195	0.8	20	30	14	3/8"-24
SDR10P25R4RR	1/2	13	2500	3.0	1.36	7.9	200	0.8	20	30	14	1/2"-20
1 hp (0.75 kW) – Keyless Chuck												
SDR10P7RK4R	1/2	13	700	3.1	9.5	9.5	241	0.8	20	30	14	3/8"-24
SDR10P20RK3R	3/8	10	2000	2.6	1.15	7.6	195	0.8	20	30	14	3/8"-24
SDR10P20RK4R	1/2	13	2000	2.8	1.27	7.6	195	0.8	20	30	14	1/2"-20
SDR10P25RK3R	3/8	10	2500	2.6	1.15	7.6	195	0.8	20	30	14	3/8"-24
SDR10P25RK4R	1/2	13	2500	2.8	27	7.6	195	0.8	20	30	14	1/2"-20



General: Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure
Standard Equipment: Parts List • Safety and Instruction Manual • 3-jaw Chuck and Key • Comfort Grip

www.dobcoeqp.com
 sales@dobcoeqp.com
 905-672-5557
 DOBCO EQUIPMENT LTD.

DOBCO EQUIPMENT LTD.
 905-672-5557
 sales@dobcoeqp.com
 www.dobcoeqp.com

Rapid Reverse Signature Series Screwdrivers



SSD4P26SRR



SSD4P26PRR



SSD10P20SRR



SSD10P20PRR

Features:

- Rapid Reverse
- Feathering Trigger (Teasing)
- Ergonomic Grip
- 1/4" Quick Change
- Light Weight Aluminum Housing
- Low Noise
- Easy to Maintain 'Drop-in Motor'
- Stall Drive or Positive Clutch
- Fast and Convenient Reversing with Top Button
- Momentary Reverse or Twist-Lock Constant Reverse



Model Number	Max Torque (Soft Joint)		Free Speed rpm	Weight		Length		Side To Center		Air Consumption		
	in lb	Nm		lb	kg	in	mm	in	mm	cfm	l/s	
0.4 hp (0.3 kW) – Stall Pistol Grip												
SSD4P18SRR	26	2.9	1800	1.4	0.6	5.2	127	0.7	17	20	10	
SSD4P26SRR	20	2.3	2600	1.4	0.6	5.2	127	0.7	17	20	10	
0.4 hp (0.3 kW) – Positive Clutch Pistol Grip												
SSD4P18PRR	26	2.9	1800	1.7	0.7	6.7	165	0.7	17	20	10	
SSD4P26PRR	20	2.3	2600	1.7	0.7	6.7	165	0.7	17	20	10	
0.6 hp (0.45 kW) – Stall Pistol Grip												
SSD6P20SRR	55	6.2	2000	2.0	0.90	5.8	146	0.8	20	25	12	
0.6 hp (0.45 kW) – Positive Clutch Pistol Grip – High Torque												
SSD6P20PSRR	55	6.2	2000	2.2	0.98	6.8	171	0.8	20	25	12	
SSD6P25PSRR	40	4.5	2500	2.2	0.98	6.8	171	0.8	20	25	12	
1 hp (0.75 kW) – Stall Pistol Grip												
SSD10P20SRR	80	9.0	2000	2.2	0.98	6.5	165	0.8	20	30	14	
1 hp (0.75 kW) – Positive Clutch Pistol Grip – Medium Torque												
SSD10P20PRR	70	7.9	2000	2.4	1.07	7.3	185	0.8	20	30	14	
SSD10P25PRR	50	5.7	2500	2.4	1.07	7.3	185	0.8	20	30	14	



General: Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure
Standard Equipment: Parts List • Safety and Instruction Manual • Comfort Grip

www.dobcoeqp.com
 sales@dobcoeqp.com
 905-672-5557
 DOBCO EQUIPMENT LTD.

DOBCO EQUIPMENT LTD.
 905-672-5557
 sales@dobcoeqp.com
 www.dobcoeqp.com

Rapid Reverse Signature Series Impact Driver



ID375AP-2QRR



Features:

- Rapid Reverse
- High Power to Weight Ratio
- Long Life Impact Assembly
- Smooth Impacting that creates Minimal Torque Reaction

Model Number	Drive Size in	Working Torque Range ¹		Maximum Torque		Blows Per Minute	Free Speed rpm	Weight		Length		Side To Center		Socket Retainer Style
		ft lb	Nm	ft lb	Nm			lb	kg	in	mm	in	mm	

Pistol Grip Impact Driver

ID375AP-2QRR	1/4	10-55	13-75	60	80	5000	4000	2.5	1.1	8.5	216	085	21	1/4" QC
--------------	-----	-------	-------	----	----	------	------	-----	-----	-----	-----	-----	----	---------

¹ Maximum working torque determined by 5 second rundown on appropriate Skidmore-Wilhelm Torque-Tension Tester.
General: Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure
Standard Equipment: Parts List • Safety and Instruction Manual

Sioux Swivel

Allows the air hose to rotate 360° on 2 axes.



1338-25



1338FC-25



Part Number	Description
1338-25	1/4" non-regulated air swivel connector with safety pin
1338-38	3/8" non-regulated air swivel connector with safety pin
1338-50	1/2" non-regulated air swivel connector with safety pin
1338FC-25	1/4" regulated air swivel connector with safety pin



Dobco Equipment Limited
 1-2430 Lucknow Drive,
 Mississauga, Ontario
 L5S 1V3 Canada

905.672.5557

sales@dobcoeqp.com